



Stainless Steel Braided Flanged Pump Connectors

KEY FEATURES:

- Designed to absorb vibration in piping systems
- 321 or 316L stainless steel corrugated hose
- 304L or 316L stainless steel braid
- ASTM A36 Carbon Steel Class 150 Slip-on Plate Flanges



Size, (in.)	Part number	Overall Length, (in.)	Working Pressure at 70°F, (PSIG)*	Flange Thickness, (in.)	Approx. Weight, (lbs)
2"	PFPC-032	9	475	5/8"	11.00
2-1/2"	PFPC-040	9	350	5/8"	14.00
3"	PFPC-048	9	300	5/8"	15.00
4"	PFPC-064	9	250	5/8"	20.00
5"	PFPC-080	11	175	3/4"	28.00
6"	PFPC-096	11	165	3/4"	33.00
8"	PFPC-128	12	234	1"	52.00
10"	PFPC-160	13	230	1"	74.00
12"	PFPC-192	14	161	1"	100.00

- Sizes 2" to 6" supplied with plain weave braid
- Sizes 8" to 12" supplied with braided braid to allow for higher Working Pressure and braid coverage
- See Penflex products catalog for hose dimensions and braid constructions
- Consult Penflex products catalog for further details on design, installation and use, temperature adjustment factors, and other technical specifications.



800-232-3539 610-367-2260 Fax 877-647-4011 www.penflex.com sales@penflex.com