



GAMMA™-FLEX OVAC

Corrugated Oilfield Suction Hose

Texcel's exclusive design for rugged oilfield service where full suction and working pressures are required. Corrugated cover for improved flexibility.



TECHNICAL DATA

Tube	Black, specially compounded elastomer; low oil swell	
Cover	Black, SBR/Nitrile blend compounded for oil and ozone resistance (corrugated)	
Reinforcement	High tensile tire cord plies; dual helix wire	
Safety Factor	4:1	
Temperature	-20°F to +180°F	
Branding	TEXCEL® GAMMA™-FLEX OVAC - FLEXIBLE OILFIELD SUCTION HOSE NOT FOR REFINED FUELS 150 PSI W.P.	
Safety Note	Not recommended for refined petroleum products	
Features	Exceptional flexibility	

I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Ft.
2"	GOV15F1-2.0	2- ³⁰ / ₆₄ "	100'	150	29	2"	1.05
3"	GOV15F1-3.0	3- ³² / ₆₄ "	100'	150	29	3"	1.64
4"	GOV15F1-4.0	4- ³⁶ / ₆₄ "	100'	150	29	4"	2.58
6"	GOV15F1-6.0	6- ⁵¹ / ₆₄ "	100'	150	29	8"	4.75